

### Product Features

- Universal input voltage / Full range: 90~305Vac;
- Constant power design, output current programming adjustable;
- (M types) offline programmable, (V types) output current adjustable by built-in potentiometer;
- 3-in-1 dimmable: 0~10Vdc, PWM, Timer dimming. Dim-to-off;
- Constant lumen output
- Output and Dimming Signal Isolating
- Surge protection: 5KV line-line, 10KV line-earth;
- Protections: SCP, OVP, OTP;
- IP67 design for indoor and outdoor applications;
- Suitable for dry / damp / wet locations;
- 5 years warranty.

### Application

- Suitable for LED roadway lighting, plant lighting, industrial lighting, landscape lighting, etc.



### DESCRIPTION

The X6-150W series is 150W outdoor offline programmable LED driver that operates in constant current with high PF value and universal input voltage range 90~305Vac model. Offline Monitored by dimming cable connected with an USB kit programming device, the fully programmed drivers offer all dimming, dim-to-off, constant lumen output options and a wide range of output current in a single driver, which deliver maximum flexibility with customized operating settings and intelligent control options for lighting manufacturers, as one driver can be programmed for many different luminaire designs. X6 provides built-in timer dimming schedules further increasing the energy savings and CO<sub>2</sub> reductions achieved with LED lighting. It also helps clients to improve the management of logistics and stock. The compact metal case and high efficiency enables the driver to operating with high reliability, and extending product lifetime. Overall protection is provided against lightning surge, output over voltage, short circuit, and over temperature, to ensure low failure rate.

### MODELS

Model Number [1]	Max Output Power (W)	Output Voltage Range (Vdc)	Full Power Output Voltage Range (Vdc)	Full Power Current Adjustable Range (A)	Default Output Current Setting(A)	Typical Efficiency [2]	PF
X6-150X041	150	20-41	28-41	3.66-5.40	4.20	91%	0.96
X6-150X062	150	38-62	42-62	2.42-3.60	3.15	91%	0.96
X6-150X108	150	54-108	71-108	1.40-2.10	2.10	92%	0.96
X6-150X143	150	80-143	100-143	1.05-1.5	1.05	92%	0.96
X6-150X214	150	107-214	143-214	0.70-1.05	0.70	92%	0.96

### Notes:


[1]. X can be M or V. X=M means dimmable and offline programmable, The adjustable lout range: 10%-100% I<sub>max</sub>;

X=V means non-dimmable and output current adjusted by built-in potentiometer.

[2]. Output current adjustable range with constant power at max output power;

[3]. All specifications are measured at 25°C ambient temperature, input voltage 230Vac, and the typical value tested by full load, if no specific note.

### OPERATING AREA I-V



Notes: X=V is suitable for the right area of the dotted line; X=M is suitable for the solid line contain area.

### INPUT SPECIFICATIONS

Parameter	Min.	Typ.	Max.	Notes
Input Voltage	90Vac	100-277Vac	305Vac	
Input Frequency	47Hz	50/60	63Hz	
Leakage Current	-	-	0.70mA	277Vac/60Hz
Input AC Current	-	-	2.0A	100-277Vac & full load
Inrush Current	-	-	75A	230Vac & full load
Standby Power Consumption			2W	
Power Factor	0.97	0.99	-	115Vac, 50-60Hz, full load
	0.95	0.97		230Vac, 50-60Hz, full load
	0.92	0.95		277Vac, 50-60Hz, full load
THD	-	5%	10%	100-240Vac, 50-60Hz, 50%-100% load
	-	-	10%	277Vac, 50-60Hz, 70%-100% load

### OUTPUT SPECIFICATIONS

Parameter	Min.	Typ.	Max.	Notes
Output Current Tolerance	-5%Iset	-	5%Iset	
Output Current Setting Range (A)				The 'M type' adjustable lout range: 10%-100% I <sub>max</sub> ,
X6-150X041	2.70		5.40	
X6-150X062	1.80		3.60	
X6-150X108	1.05	-	2.10	
X6-150X143	0.75		1.50	
X6-150X214	0.52		1.05	
Output Current Setting Range with Constant Power				
X6-150X041	3.66		5.40	
X6-150X062	2.42	-	3.60	
X6-150X108	1.40		2.10	
X6-150X143	1.05		1.50	
X6-150X214	0.70		1.05	
Total Output Current Ripple(pk-pk)	-	5%	10%	20MHz BW, full load & LED load, the ripple would be tiny different under different LED load.
Startup Overshoot Current	-	-	10%	100~277Vac & 100% Load, load is LED
No Load Output Voltage				
X6-150X041			50	
X6-150X062	-	-	70	
X6-150X108			120	
X6-150X143			160	

X6-150X214			240	
Line Regulation	-1%	-	1%	25°C±10°C ambient temperature, input voltage changes from 100Vac to 277Vac.
Load Regulation	-3%	-	3%	25°C±10°C ambient temperature, Input Voltage 230Vac, load changes from 60% to 100%.
Turn-on Delay Time	-	1S	2S	115Vac, 100% load
	-		0.5S	230Vac, 100% load

### GENERAL SPECIFICATIONS

Parameter	Min.	Typ.	Max.	Notes
Efficiency @115Vac				Measured at full load and 25°C ambient temperature
X6-150X041				
Io=3.66	86%	88%		
Io=5.40	86%	88%		
X6-150X062				
Io=2.42	86%	88%		
Io=3.60	86%	88%		
X6-150X108				
Io=1.40	87%	89%		
Io=2.10	87%	89%		
X6-150X143				
Io=1.05	89%	90%		
Io=1.50	89%	90%		
X6-150X214				Measured at full load and 25°C ambient temperature
Io=0.70	89%	90%		
Io=1.05	89%	90%		
Efficiency @230Vac				
X6-150X041				
Io=3.66	88%	90%		
Io=5.40	88%	90%		
X6-150X062				
Io=2.42	89%	91%		
Io=3.60	89%	91%		
X6-150X108				
Io=1.40	90%	92%		
Io=2.10	90%	92%		
X6-150X143				
Io=1.05	90%	92%		
Io=1.50	90%	92%		
X6-150X214				Measured at full load and 25°C ambient temperature
Io=0.70	90%	92%		
Io=1.05	90%	92%		
Efficiency @277Vac				
X6-150X041				
Io=3.66	88%	90%		
Io=5.40	88%	90%		
X6-150X062				
Io=2.42	89%	91%		
Io=3.60	89%	91%		
X6-150X108				
Io=1.40	90%	92%		
Io=2.10	90%	92%		
X6-150X143				

I <sub>o</sub> =1.05		90.5%	92.5%		
I <sub>o</sub> =1.50		90.5%	92.5%		
X6-150X214					
I <sub>o</sub> =0.70		90.5%	92.5%		
I <sub>o</sub> =1.05		90.5%	92.5%		
Dielectric Strength	Input-Output	-	3750Vac	-	Max 5mA/60S
	Input-PE	-	1600Vac	-	
	Output-PE	-	1600Vac	-	
Grounding Resistance		-	-	0.1Ω	25A/60S, under 25°C±10°C ambient temperature
Insulation Resistance		50MΩ	-	-	Input-Output, Input-PE, Output-PE, 500Vdc/60S/25°C/70%RH
MTBF		-	200000Hrs	-	25°C±10°C ambient temperature, 230Vac, 80% load (MIL-HDBK-217F)
Lifetime		-	50000Hrs	-	230Vac&100% load, 75°C case temperature, refer to lifetime curve for details
Ambient Temperature		-40°C		+60°C	230Vac&100% load
Operating Case Temperature for Safety T <sub>c_s</sub>		-40°C	-	+90°C	
Operating Case Temperature for Warranty T <sub>c_s</sub>		-40°C	-	+75°C	5 years warranty case temperature Humidity: 10% to 95% RH
Storage Temperature		-40°C	-	+85°C	Humidity: 5% to 100% RH
Dimensions (LxWxH)mm		L173.6*W68*H37			
Net Weight		800±100g/PCS			
Package		L500mm*W370mm*H160mm; 10PCS/Ctn, Gross Weight: 8Kg			

### DIMMING

Parameter		Min.	Typ.	Max.	Notes
0~10V Absolute Maximum Voltage on the V <sub>dim</sub> (+) Pin		-	10V	-	
0~10V Source Current on V <sub>dim</sub> (+)Pin		-	0.1mA	0.2mA	
Dimming Output Range	X6-150M041 X6-150M062 X6-150M108 X6-150M143 X6-150M214	10%I <sub>max</sub>	-	100%I <sub>max</sub>	I <sub>max</sub> =5.40A I <sub>max</sub> =3.60A I <sub>max</sub> =2.10A I <sub>max</sub> =1.50A I <sub>max</sub> =1.05A
	X6-150M041 X6-150M062 X6-150M108 X6-150M143 X6-150M214	0.54 0.36 0.21 0.15 0.11	-	5.40 3.60 2.10 1.50 1.05	
Recommended Dimming Range for 0-10V		0V	-	10V	Default 0-10V/ PWM Dimming(0-10V,0-9V,0-5V,0-3.3V and Forward and reverse dimming can be customized as request)
PWM_in High Level		9.7V	-	10.3V	
PWM_in Low Level		0V	-	0.3V	
PWM_in Frequency Range		200Hz		2000Hz	
PWM_in Duty Cycle		1%	-	99%	

### SAFTY STANDARDS

Safety Category	Country / Territory	Standards	Approved
CCC	China	GB19510.1, GB19510.14	√
CE	Europe	EN61347-1, EN61347-2-13	√
		EN62493	√
		EN62384	√
ENEC			
CB	CB Countries	IEC61347-1, IEC61347-2-13	√
BIS	India	IS 15885(PART 2/SEC 13)	
UL	USA	UL 8750	√
CUL	Canada	CSA C22.2 No.250.13	√
KC	South Korea	K61347-1, K61347-2-13	
PSE	Japan	J61347-1, J61347-2-13	
SAA	Australia	AS/NZS IEC 61347.2.13	√
		AS/NZS 61347.1	√


### EMC COMPLIANCE

EMC Category	Country / Territory	Standards	Approved
CCC	China	GB/T 17743, GB 17625.1	√
CE	Europe	EN 55015	√
		EN 61000-3-2, EN 61000-3-3	√
		EN61000-4-2,3,4,5,6,11	√
		EN 61547	√
KC	South Korea	K61547	
		K00015	
PSE	Japan	J55015	
FCC	USA	FCC part 15	


### NOTE:

This LED driver meets the EMI specifications above, but as a component of a luminaire, end customer need to identify the EMI performance of a luminaire including LED driver, other devices connected to the driver and on the luminaire itself.


### INRUSH CURRENT WAVEFORM



### DERATING CURVE




### OUTPUT POWER VS INPUT VOLTAGE






### LIFETIME VS CASE TEMPERATURE




### EFFICIENCY VS LOAD






### POWER FACTOR VS LOAD




### TOTAL HARMONIC DISTORTION



### PROTECTIONS


Parameter	Notes
Over Temperature Protection	Decreases output current, returning to normal after over temperature is removed. The max derating could be 30% (typ.).
Short Circuit Protection	Hiccup mode and auto recovery. No damage will occur when any output is short circuited. The output shall return to normal when the fault condition is removed.
Output Over Voltage Protection	Run into protection model when output voltage exceeds limit, and return to normal when the fault

### 0-10V/PWM DIMMING




### MECHANICAL OUTLINE

X6-150M types



X6-150V types



Wire	Specification	Note
Input	17AWG*3C SJOW external diameter: 8.3mm L=300±20mm, peel length 35mm, Tin-dip length 10mm	for CCC/CE/UL
Output	17AWG*2C SJOW external diameter: 7.7mm L=300±20mm, peel length 35mm, Tin-dip length 10mm	for CCC/CE/UL
Dimming	UL2733 22AWG*2C external diameter: 5.45mm L=350±10mm, peel length 35mm, Tin-dip 10mm	X = M

**REVISION HISTORY**

Version	Description of Change		Date	Notes
	Before	Now		
A.1	—	Datasheets Release	2019-06-21	