



REV.	DESCRIPTION	DRAWN	DATE
1	INITIAL RELEASE	TIM	2020/06/03

Notes:

1. ELECTRICAL
 - 1.1 Current Rating: 2A
 - 1.2 Voltage Rating: 30V
 - 1.3 Contact Resistance: 50mΩ Max. at working height
2. MECHANICAL
 - 2.1 Spring Force: 45g±15g at working height
 - 2.2 Durability: 10,000 cycles
3. To avoid arcing issue, the adaptor start to power supply after connector mated fully
4. Based on the Engineer drawing, shall not exceed on the working height the maximum allowed compress
5. To ensure the best usage, please operate it based supply after connector mated fully

How to order:

303B-411806-254-XX
1

- 1 pin count: xx= 04~10
(Please contact with sales for the pins count available)

5	CAP	Thermoplastic, Black
4	SPRING	Stainless steel
3	BARREL	Brass, gold plating under nickel over all
2	PISTON	Copper alloy, 10u" gold plating on contact area, gold plating under nickel over all
1	HOUSING	Thermoplastic, UL94V-0, Black
NO.	PART NAME	DESCRIPTION

UNLESS OTHERWISE SPECIFIED TOLERANCE

UNIT:	DECIMAL	LINEAR	ANGLES
mm	X.	±0.50	±5°
	X.X	±0.25	±3°
	X.XX	±0.12	±1°



DRAWN	Tim	2020/06/03	DRAWN NAME:	Pogo Pin, R/A, XX Pin, 2.54P, 10u" 2.5H, Dip, CAP	
CHECKED	Fros	2020/06/03	PRODUCT NO.	303B-411806-254-XX	
APPROVED	Ken	2020/06/03	SCALE	SHEET	SIZE
			4/1	1/1	A4
			FILE NAME	303B-411806-254-XX_B_1	