



Model	ASLAN-W922C-IP	ASLAN-W922C-6300G4	ASLAN-W915C-6300G4	ASLAN-W919C-6300G4	ASLAN-W912C-6300G4	ASLAN-W910C-6300G4
Dimensions (W x H x D)	620 x 423 x 62 mm	536 x 332 x 55.5 mm	404 x 255 x 56.3 mm	470 x 295 x 56.2 mm	306 x 206 x 76.5 mm	255 x 175 x 76.5 mm
CPU	6 th Gen. Intel® Core™ i5-6300U 2.4GHz	6 th Gen. Intel® Core™ i5-6300U 2.4GHz	6 th Gen. Intel® Core™ i5-6300U 2.4GHz	6 th Gen. Intel® Core™ i5-6300U 2.4GHz	6 th Gen. Intel® Core™ i5-6300U 2.4GHz	6 th Gen. Intel® Core™ i5-6300U 2.4GHz
Chipsets	-	-	-	-	-	-
Memory	4GB DDR4 installed	4GB DDR4 installed	4GB DDR4 installed	4GB DDR4 installed	4GB DDR4 installed	4GB DDR4 installed
LCD Display	21.5", 1920 x 1080	21.5", 1920 x 1080	15.6", 1366 x 768	18.5", 1366 x 768	11.6", 1920 x 1080	10.1", 1280 x 800
Video Output	HDMI/VGA	HDMI/VGA	HDMI/VGA	HDMI/VGA	HDMI/VGA	HDMI/VGA
Audio	Optional	Optional	Optional	Optional	Optional	Optional
KB/MS	-	-	-	-	-	-
Ethernet	2 x GbE	2 x GbE	2 x GbE	2 x GbE	2 x GbE	2 x GbE
Mass Storage	1 x mSATA, 2 x 2.5" drive bays	1 x mSATA, 2 x 2.5" drive bays	1 x mSATA, 2 x 2.5" drive bays	1 x mSATA, 2 x 2.5" drive bays	1 x mSATA	1 x mSATA
RS-232	-	-	-	-	-	-
RS-232/422/485	2	4	4	4	2	2
Digital I/O	4in/4out(optional)	4in/4out(optional)	4in/4out(optional)	4in/4out(optional)	-	-
USB 2.0	2	-	-	-	-	-
USB 3.0/2.0	Optional	4	4	4	4	4
WIFI	mPCIe(optional)	mPCIe(optional)	mPCIe(optional)	mPCIe(optional)	mPCIe(optional)	mPCIe(optional)
Speaker	-	2 x 2W speakers (optional)	2 x 2W speakers (optional)	2 x 2W speakers (optional)	-	-
Expansion Bus	2 x mPCIe (1 half & 1 full)	2 x mPCIe (1 half & 1 full)	2 x mPCIe (1 half & 1 full)	2 x mPCIe (1 half & 1 full)	2 x mPCIe (1 half & 1 full)	2 x mPCIe (1 half & 1 full)
Power Input	DC 9 ~ 36V	DC 9 ~ 36V	DC 9 ~ 36V	DC 9 ~ 36V	DC 12 ~ 28V	DC 12 ~ 28V
Operating Temperature	-10 ~ 50°C	-20 ~ 55°C	-20 ~ 55°C	-20 ~ 55°C	-20 ~ 55°C	-20 ~ 55°C

Wide-Screen HMI



Model	ASLAN-W812C-2930G2	ASLAN-W810C-2930G2	ASLAN-W722C-1900G4	ASLAN-W719C-1900G4	ASLAN-W715C-1900G4	ASLAN-917 Series R/C
Dimensions (W x H x D)	306 x 206 x 39.5 mm	255 x 175 x 39.5 mm	536 x 332 x 48.4 mm	470 x 295 x 49.2 mm	404 x 255 x 49.2 mm	420 x 358 x 62.2 mm
CPU	Intel® N2930 Quad-Core™ 1.83GHz	Intel® N2930 Quad-Core™ 1.83GHz	Intel® J1900 Quad-Core™ 2.0GHz	Intel® J1900 Quad-Core™ 2.0GHz	Intel® J1900 Quad-Core™ 2.0GHz	6 th Gen. Intel® Core™ i5-6300U 2.4GHz
Chipsets	-	-	-	-	-	-
Memory	2GB DDR3L installed	2GB DDR3L installed	4GB DDR3L installed	4GB DDR3L installed	4GB DDR3L installed	4GB DDR4 installed
LCD Display	11.6", 1920 x 1080	10.1", 1280 x 800	21.5", 1920 x 1080	18.5", 1366 x 768	15.6", 1366 x 768	17", 1280 x 1024
Video Output	DVI-I	DVI-I	DVI-I	DVI-I	DVI-I	HDMI/VGA
Audio	Mic-in/Line-out	Mic-in/Line-out	-	-	-	Optional
KB/MS	-	-	-	-	-	-
Ethernet	2 x GbE	2 x GbE	3 x GbE	3 x GbE	3 x GbE	2 x GbE
Mass Storage	1 x mSATA	1 x mSATA	2 x 2.5" drive bays	2 x 2.5" drive bays	2 x 2.5" drive bays	1 x mSATA, 2 x 2.5" drive bays
RS-232	-	-	2	2	2	-
RS-232/422/485	-	-	2	2	2	4
Digital I/O	-	-	-	-	-	-
USB 2.0	1	1	3	3	3	-
USB 3.0/2.0	1	1	1	1	1	4
WIFI	mPCIe(optional)	mPCIe(optional)	mPCIe(optional)	mPCIe(optional)	mPCIe(optional)	mPCIe(optional)
Speaker	-	-	2 x 2W speakers (optional)	2 x 2W speakers (optional)	2 x 2W speakers (optional)	-
Expansion Bus	2 x mPCIe (1 half & 1 full)	2 x mPCIe (1 half & 1 full)	1 x mPCIe (full)	1 x mPCIe (full)	1 x mPCIe (full)	2 x mPCIe (1 half & 1 full)
Power Input	DC 12V	DC 12V	DC 9 ~ 36V	DC 9 ~ 36V	DC 9 ~ 36V	DC 9 ~ 36V
Operating Temperature	-10 ~ 55°C	-10 ~ 60°C	-20 ~ 55°C	-20 ~ 55°C	-20 ~ 55°C	-20 ~ 55°C