

# **EGX-MXM-T1000**

Mobile PCI Express Module with NVIDIA<sup>®</sup> Ouadro<sup>®</sup> Embedded T1000

#### **Features**

- NVIDIA<sup>®</sup> Quadro<sup>®</sup> T1000 embedded graphics
- Standard MXM 3.1 Type A (82 x 70 mm)
- 896 CUDA cores,
- 2.6 TFLOPS peak FP32 performance
- 4GB GDDR6 memory, 128-bit
- 192GB/s maximal memory bandwidth
- Support up to 4 DP 1.4a displays, 50W TGP
- 5-year availability



### Introduction

The EGX-MXM-T1000 module features advanced NVIDIA<sup>®</sup> Turing™ GPU technology in MXM 3.1 Type A form factor. It's compact, slim and reliable design makes it suitable for mission critical environment. EGX-MXM-T1000 provides improved performance per watt. This MXM GPU module offers a flexible and easy solution for deep learning solutions for applications including medical, image processing, and gaming applications.

# **Ordering Information**

• EGX-MXM-T1000

Ò.

EMBEDDED

NVIDIA<sup>®</sup> Quadro<sup>®</sup> T1000 Embedded Graphics, MXM 3.1 type A, 82 x 70mm, PCIe x16 Gen3

## **Specifications**

| Model Name               | EGX-MXM-T1000                                                                  |
|--------------------------|--------------------------------------------------------------------------------|
| Graphic Core             |                                                                                |
| GPU                      | Quadro <sup>®</sup> T1000                                                      |
| Memory                   | 4GB GDDR6 memory, 128-bit,<br>Bandwidth: 192 GB/s                              |
| GPGPU Computing          |                                                                                |
| CUDA Cores               | 896 CUDA cores,<br>2.6 TFLOPS Peak FP32 performance                            |
| Compute API              | CUDA Toolkit 8.0 and above,<br>CUDA Compute version 6.1 and above, OpenCL™ 1.2 |
| Graphics API             | DirectX <sup>®</sup> 12, OpenGL 4.6,<br>Vulkan 1.0 API                         |
| Display                  |                                                                                |
| Display Outputs          | 4x DisplayPort 1.4a digital video outputs<br>4K at 120Hz or 8K at 60Hz         |
| Interface                | MXM 3.1, PCI Express Gen3 x16 support                                          |
| Mechanicals              |                                                                                |
| Dimensions               | 82 (W) × 70 (D) × 4.8 (H) mm                                                   |
| Form Factor              | Standard MXM 3.1 Type A                                                        |
| Environmental            |                                                                                |
| Operating Temp.          | Standard: 0°C to 55°C                                                          |
| Storage Temp.            | -40°C to 85°C                                                                  |
| Module Power Consumption | 50W TGP                                                                        |
| SW Support               |                                                                                |
| OS Support               | Windows 10 & Linux Drivers, 64-bit                                             |



Windows 10 & Linux Drivers, 64-bit

Singel 3 | B-2550 Kontich | Belgium | Tel. +32 (0)3 458 30 33 info@alcom.be | www.alcom.be Rivium 1e straat 52 | 2909 LE Capelle aan den IJssel | The Netherlands Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl