

# SBC35-RPL

3.5" Single Board Computer with 13th Gen Intel® Core™ i7/i5/i3/Celeron® Processor

## Features

- 13th Gen Intel® Core™ i7/i5/i3/Celeron® processor
- Dual-channel DDR5 4800MHz memory up to 64GB
- Four independent display: eDP/LVDS (default eDP) HDMI, DP, USB Type-C
- Dual GbE ports: 1GbE (Intel® I219-V), 1x 2.5GbE (Intel® I225-V)
- SBC-FM board expansion: PCIe x1, PCIe Gen4 x4, USB3.0/2.0, LPC
- TPM 2.0 (option)



## Ordering Information

PN	Model Name	CPU	Memory	DP	HDMI	LCD	USB Type-C	COM	SATA	USB2.0	USB3.0	M.2	SBC-FM	TPM
91-47300-00XX	SBC35-RPL	i3-1315UE	DDR5 SO-DIMM 4800 MHz	1	1	eDP	1	4	1	3	2	3	Support	Support (option)

## Packing Lists

PN	Description	QTY
91-47300-00XX	SBC35-RPL	1
58-10515-0000	M.2 screw kit	1
58-10514-0000	Thermal kit	1

## Optional Accessories

PN	Description
32-21014-0000-A0	CPU cooler for 28W CPU
32-21015-0000-A0	Passive Heatsink for 15W CPU
30-21363-0000-A0	USB 2.0 Type A connectorx1
30-21534-0010-A0	RS-232x2+ RS-232/RS-485/RS-422x2
30-22122-0000-A0	DI/DOx8-bits +Audio +USB 2.0x2
30-22121-0000-A0	SATA+ SATA Power
91-49076-0010	SBC35-RPL LVDS FPC


## Embedded OS

PN	Description
92-56094-0010	Windows 10 IoT Ent LTSC 2021 High End PKEA
92-56094-2010	Windows 10 IoT Ent LTSC 2021 Value PKEA
92-56094-4010	Windows 10 IoT Ent LTSC 2021 Entry PKEA
92-56101-0010	Windows 11 IoT Ent 2022 High End PKEA
92-56101-2010	Windows 11 IoT Ent 2022 Value PKEA
92-56101-4010	Windows 11 IoT Ent 2022 Entry PKEA


## Specifications

Model	SBC35-RPL
<b>Processor System</b>	
CPU	Intel® Core™ i7/i5/i3/Celeron® processor
Memory	Dual-channel DDR5 SO-DIMMs 4800MHz, up to 64GB
Operating Systems	Windows 10/ 11 IoT Enterprise LTSC 21H2 (64-bit) Ubuntu desktop 22.04 LTS (Support by project)
<b>Display</b>	
Type-C	1
eDP	1 (co-lay LVDS by option)
HDMI	1
DisplayPort	1
<b>Ethernet</b>	
Gbe Port	2
Controller/ Frequency	1x Intel® I219-V, 1Gbps/ 100Mbps / 10Mbps 1x Intel® I225-V, 2.5Gps / 1Gbps/ 100Mbps / 10Mbps
<b>I/O Interfaces</b>	
USB	2x USB 3.2 Gen 2x1 ports (10Gbps) (rear I/O) 2x USB 2.0 via headers
USB Type-C	1x USB TYPE-C (USB 3.2, DP, Power delivery 5V, 3A)
COM	2x RS-232/422/485 pin headers 3x RS-232 pin headers
Serial ATA	1x SATA 6Gb/s ports w/ 5V SATA power
Audio	Realtek ALC888S 1x line-in, 1x line-out, MIC-in
Expansion Slots	M.2 2280 M Key (PCIe x4) M.2 2230 E Key (PCIe x1, USB 2.0) M.2 3042 B-key (USB 3.0/2.0)
TPM	TPM 2.0 (option)
DI/ DO	8 DI and 8 DO
<b>FM board expansion</b>	
PCIex1	1
PCIe x4	1
USB3.0/2.0	1
LPC	Yes
<b>Mechanical and Environment</b>	
Form Factor	3.5" Single Board Computer
Dimension	5.75" x 4" (146mm x 102mm)
Power Supply	12V-24V Reserve DC JACK connector (option)
Operating Temperature	0 to 60 °C Fanless, reserve 4-pin smart fan connector (12V) For 28W SKU.
Storage Temperature	-40°C to 85°C
<b>Certification</b>	
EMC	CE & FCC Class B
ESD	Contact +/-8 KV, Air +/-12 KV

## Product Illustration



## Block Diagram



\* Default by BOM change, contact with your local sales to support option.

All products and company names listed are trademarks or trade names of their respective companies. Updated Jul. 23, 2024. ©2024 ADLINK Technology, Inc. All Rights Reserved. All pricing and specifications are subject to change without further notice.