



Features /

Quad-core Cortex-A73 and Dual-core Cortex-A53

AMLOGIC A311D Processor, Machine Vision Application System

- ARM Mali-G52 MP6 GPU, 5.0 TOPS NPU
- Onboard 2GB DDR3 (Option 4GB)
- HDMI Display Outputs
- Integrated Camera Interfaces
- One PoE Port
- Support Ubuntu 20.04

Specifications /

System	
CPU	AMLOGIC, A311D, Quad-core Cortex-A73 and Dual-core Cortex-A53
System Memory	Onboard 2GB DDR3
I/O Interface	
USB	2 x USB 2.0 (Type A) stack ports-With lock 1 x USB 2.0 (Type A) stack port (Internal) 1 x OTG
Serial/Parallel	1 x RS-232/RS-485/RS-422, DB9
Display	1 x HDMI
LAN	2 x Gigabit Ethernet port by Intel I210-With lock 1 x Gigabit IEEE 802.3af (15.4W) PoE ports-With lock
Digital I/O	4 x Isolated DI and 4-CH Isolated DO (NPN/PNP Mode select)
Trigger I/O	2 x Isolated Trigger_In 1 x Isolated Trigger_Out
Lighting	2 x Lighting Control Output
Power	1 x DC In 2-pin Power Connector
Others	1 x Reset Button 1 x Micro SIM Slot

Storage Space	
Storage	Onboard 32GB eMMC


On Board Expansion Bus 1 x Full-size Mini-PCle slot (USB/PEle Signal)


Power Input	DC 9~36V Power Input	
Mechanical		
Construction	Aluminum Heatsink and Steel Chassis	
Mounting	DIN Rail Mount	
Dimensions	173.6 x 429 x 451.2 mm	
Environmental		


Environmental	
Operating Temperature	-20~60°C
Storage Temperature	-40~85°C
Storage Humidity	10 to 90%@ 40°C, non-condensing
Certificate	Meet CE/FCC Class A, RoHs


Linux Ubuntu
















Singel 3 | B-2550 Kontich | Belgium | Tel. +32 (0)3 458 30 33 info@alcom.be | www.alcom.be | www.alcom.be | Rivium 1e straat 52 | 2909 LE Capelle aan den IJssel | The Netherlands Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl

V 1.0