



EMX-RPLP

13th Gen Intel® Core™ SoC i7/i5/i3 & Celeron BGA Processor Mini ITX Motherboard

- > Onboard 13th Gen. Intel® Core™ SoC i7/i5/i3 & Celeron® BGA Processor
- > 2 x 262-pin DDR5 4800MHz SO-DIMM supports up to 64GB (non ECC only)
- > 2 x DP++, 2 x DP, 1 x LVDS, 1 x eDP (Maximum: 6 for quadruple independent displays)
- > 3 x Intel® I226LM 2.5 Gigabit Ethernet
- > 1 x Intel® I219LM Gigabit Ethernet PHY
- > Realtek ALC888S
- > TI TPA3113D2PWP Stereo Class-D 6W x2 Audio Amplifier
- > 1 x M.2 Type B 3042/3052 (with 1 x PCIe x1 (default), USB 2.0, USB 3.2 Gen2 with 1 x SIM card slot support WWAN+GNSS
- > 1 x M.2 Key E 2230 support Wi-Fi module and CNVi (1 x PCIe x1 & USB 2.0 Signal)
- > 1 x M.2 Key B 2242 (SATA Signal, shared with SATA2) slot support SSD storage
- > 1 x M.2 Key M 2280 (PCI-e x4) slot for storage NVMe SSD
- > H-series: 1 x PCIe x8 Gen 4 slot (with Redriver mux (DS160PR421 3.2US x1 & DS160PR412 3.2US x1))
- > P/U-series: 1 x PCIe x4 Gen 4 slot (with Redriver mux (DS160PR421 3.2US x1 & DS160PR412 3.2US x1))
- > GPIO 16bit
- > Onboard NuvoTon NPCT754AADYX support TPM 2.0
- > Support Line-out & Mic-in & Front audio pin-header
- > DC in +12V~24V

+ Spec

-System Information-	
Processor	Onboard Raptor Lake-P 13th Intel® Core™ SoC i7/i5/i3/Celeron Processor (TDP: 15~45W) H-Series: 25~45W, P-Series: 20~28W, U-Series: 12~15W
System Memory	2 x 262-pin DDR5 4800 MHz SO-DIMM supports up to 64GB (non ECC only)
I/O Chipset	EC iTE IT5782VG MAX3243 for RS232, MAX13487 Transceiver & SP485 IC for RS422/485
BIOS Information	AMI uEFI BIOS, 256Mbit SPI Flash ROM
Watchdog Timer	H/W Reset: 1sec. ~ 65535sec./min. and 1sec. or 1min./step
H/W Status Monitor	CPU temperature monitoring Voltages monitoring CPU fan speed control
TPM	Onboard NuvoTon NPCT754AABYX support TPM 2.0
Expansion	
Expansion	* 1 x M.2 Type B 3042/3052 (with 1 x PCIe x1 (default), USB 2.0, USB 3.2 Gen2 with 1 x SIM card slot support WWAN+GNSS * 1 x M.2 Key E 2230 support Wi-Fi module and CNVi (1 x PCIe x1 & USB 2.0 Signal) * 1 x M.2 Key B 2242 (SATA Signal, shared with SATA2) slot support SSD storage * 1 x M.2 Key M 2280 (PCI-e x4) slot for storage NVMe SSD * H-series: 1 x PCIe x8 Gen 4 slot (with Redriver mux (DS160PR421 3.2US x1 & DS160PR412 3.2US x1)) * P/U-series: 1 x PCIe x4 Gen 4 slot (with Redriver mux (DS160PR421 3.2US x1 & DS160PR412 3.2US x1))
I/O	
USB Port	2 x USB 3.2 Gen2, 2 x USB 3.0 Gen2 at I/O 4 x USB 2.0 by pin header
COM Port	4 x RS232 2 x RS422/485
SATA	1 x SATA Power 2 x SATA III
DIO	1 x 16-bit GPIO
Display	
Graphic Chipset	Intel® Iris® Xe Graphics (For Core i5 & i7) Intel® UHD Graphics for 12th Gen Intel® Processors (For Core i3 & Celeron)
Spec. & Resolution	DP1+DP3 (DP1.4): Max: 7680 x 4329@60 Hz DP2+DP4 (DP1.4): Max: 7680 x 4329@60 Hz Single DP port (2021/2 Lab test): 5120 x 2160 @60 Hz, check Max: 7680 x 4329@60 Hz Intel resolution as below: 2 x DP++ : 1920 x 1080@60 Hz 2 x DP: 4096 x 2304@60 Hz LVDS: 1920 x 1080 Dual channel 18/24-bits LVDS (Chrontel CH7511B eDP to LVDS) eDP 4096 x 2304@60 Hz *2 x DP++, LVDS, eDP Default (Thin Mini ITX), Optional: DP3 and DP4 for full height (Maximum: 6 for quadruple independent displays)
Multiple Display	2 x DP++/2 x DP/1 x LVDS/1 x eDP (Maximum: 6 for quadruple independent displays)
LVDS	2CH 18/24bits LVDS 1920 x 1080 Chrontel. CH7511B eDP to LVDS Converter
Audio	
Audio Codec	Realtek ALC888S
Audio Interface	Support Line-out & Mic-in & Front audio pin-header
Audio Amplifier	2 x Stereo Class-D 6W Audio Amplifier
Ethernet	
LAN Chipset	3 x Intel® i226LM 2.5 Gigabit Ethernet (LAN2~4) 1 x Intel® i219LM Gigabit Ethernet PHY

	*LAN3~4 for Full height
Ethernet Interface	10/100/1000 Base-Tx GbE compatible

www.avalu.com.tw



LAN Port	4 x RJ45
Mechanical & Environmental	
Operating Temperature	0~60C (32~140°F) w/HDD/SSD, ambient with 0.5 m/s Air flow
Storage Temperature	-40 ~ 75°C (-40 ~ 167°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	0.88lbs (0.4Kgs)
Power Requirement	+12V~24V
Power Mode	AT/ATX
Dimension (L x W)	6.69" x 6.69" (170mm x 170mm)
Software Support	
OS Information	Win11 64bit, Win10 64bit Linux
Ordering Information	
Ordering Information	EMX-RPLP-A1R Intel® 13th Gen. Core™ SoC i7/i5/i3 & Celeron®BGA Processor Mini ITX Motherboard

www.avalu.com.tw



Singel 3 | B-2550 Kontich | Belgium | Tel. +32 (0)3 458 30 33
 info@alcom.be | www.alcom.be
 Rivium 1e straat 52 | 2909 LE Capelle aan den IJssel | The Netherlands
 Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl