

TQMxE41M

x86 Family



COM Express Mini Type 10 Module with Intel Atom® Processors x7000 Series, Intel® Core™ i3-N305 Processor, and Intel® Processor N Series ("Alder Lake-N" and "Amston Lake").

HIGHLIGHTS

- ▶ Intel Atom® Processors x7000E Series, Intel Atom® Processors x7000RE Series, Intel® Core™ i3-N305 Processor, and Intel® Processor N Series
- ▶ One common design for 12 CPU options
- ▶ High efficiency with 6 W to 15 W processor power
- ▶ Two independent high-resolution display outputs
- ▶ Intel® AVX256 and Intel® Deep Learning Boost support
- ▶ 2.5 Gigabit ETH, high-speed PCIe and IO
- ▶ Extended temperature and industrial use conditions (24/7) available
- ▶ CAN (Linux) (assembly option)


TECHNICAL SPECIFICATION

Supported CPUs

Intel® Core™ i3 and Intel® Processor N series ("Alder Lake-N")	Intel® Core™ i3-N305 (8-Core, 1.8/3.8 GHz, 32 EU, 15 W TDP)
	Intel® Core™ i3-N305* (8-Core, 1.0/3.8 GHz, 32 EU, 9 W cTDP)
	Intel® Processor N200 (4-Core, 1.0/3.7 GHz, 32 EU, 6 W TDP)
PC-Client Use-Conditions – C-Temp	Intel® Processor N97 (4-Core, 2.0/3.6 GHz, 24 EU, 12 W TDP)
	Intel® Processor N50 (2-Core, 1.0/3.4 GHz, 16 EU, 6 W TDP)
Intel Atom® Processors x7000E series ("Alder Lake-N")	Intel Atom® x7425E (4-Core, 1.5/3.4 GHz, 24 EU, RT, 12 W TDP)
	Intel Atom® x7213E (2-Core, 1.7/3.2 GHz, 16 EU, RT, 10 W TDP)
	Intel Atom® x7211E (2-Core, 1.0/3.2 GHz, 16 EU, RT, 6 W TDP)
Embedded Use-Conditions – C-Temp	

Based on

COM Express



Intel Atom® Processors x7000RE series ("Amston Lake")	Intel Atom® x7835RE (8-Core, 1.3/3.6 GHz, 32 EU, RT, 12 W TDP)
Industrial Use-Conditions with 24/7 – I-Temp	Intel Atom® x7433RE (4-Core, 1.5/3.4 GHz, 32 EU, RT, 9 W TDP)
	Intel Atom® x7213RE (2-Core, 2.0/3.4 GHz, 16 EU, RT, 9 W TDP)
	Intel Atom® x7211RE (2-Core, 1.0/3.2 GHz, 16 EU, RT, 6 W TDP)
Memory	LPDDR5: up to 32 GB, with In-Band-ECC option (BIOS config) eMMC: 16, 32, 64, 128, 256 GB EEPROM 32 KB
Graphics	1x eDP (4K @ 60 Hz) or Single Channel LVDS (18/24-bit) (assembly option) 1x DP++ (4K @ 60 Hz)
Additional components and controller	1x TPM 2.0 (SLB9672) (assembly option) TQMx86 board controller Hardware monitor for thermal management

Interfaces

- 1x 2.5 Gigabit Ethernet (Intel® i226)
- 2x USB 3.2 Gen2 (up to 10 Gb/s)
- 8x USB 2.0
- 4x PCIe Gen3 (up to 8 Gb/s per Lane) (div. configurations)
- 2x SATA Gen3 (up to 6 Gb/s)
- 1x HD audio (HDA)
- 1x LPC (standard) or eSPI (assembly option)
- 1x SPI (General Purpose)
- 1x SPI (for external UEFI BIOS flash)
- 1x I2C
- 1x SMBus
- 2x Serial port or
 - 1x Serial port + 1x CAN (assembly option)
- 8x GPIO

Power supply

- Main Voltage: 4.75 V – 20 V
- RTC Battery Voltage: 3 V
- Power: typ. 3 – 12 W / max. TBD


Environment

- For x7000E / N series:
 - Standard temperature: 0°C...+60°C (DTR +/- 70°C Tj CPU)
- For x7000RE series:
 - Extended temperature: -40°C...+85°C (DTR +/-110°C Tj CPU)

Form factor/ dimensions

- COM Express Mini, Type 10
- 84 mm x 55 mm

BLOCK DIAGRAM TQMxE41M



ORDERING INFORMATION

Standard configurations are listed on the website.
Custom specific configurations on request.

TQ-Systems GmbH

Mühlstraße 2 | Gut Delling | 82229 Seefeld | Germany
Tel.: +49 8153 9308-0 | info@tq-group.com | tq-group.com

tq-embedded.com