



Battery Chargers

- FSP600-1UAC01 -

for AGV & AMR

The FSP has developed a 600W charger -FSP600-1UAC01 acceptable to a full range of input voltages, with an output voltage of 50.4V-58.8V and an output current of 10.0A. The product has a streamlined appearance and a compact size of only

202*132*69mm/2.2Kg.



Battery Chargers

- FSP600-1UAC01 -

for AGV & AMR



Customization Services

- Charging voltages/currents
- Locking mechanisms/wires
- Charging curves

Application

- AGV
- AMR
- E-Bike
- Self Balancing Electric Scooters

Options

- On-board chargers: IP65 + CAN bus
- Off-board chargers: IP54 + CAN bus + handheld design

MODEL	FSP600-1UAC01
DC OUTPUT	
Output Voltage (max.)	58.8 V
Output Current (max.)	10.0 A
Output Power (max.)	600 W
Efficiency	≥ 90%
AC INPUT	
Input Voltage Range	90 Vac ~ 264 Vac
Input Current	6.0 A
Input Frequency Range	47 Hz ~ 63 Hz
MECHANICAL	
Dimensions	202 x 132 x 69 mm
Weight	2.2 kg
Cooling	Fan Cooling
COOMMUNICATION	
CAN bus (optional)	☉
APPLICATION	
On-board	EV
Off-board	AGV
ENVIRONMENTAL	
Enclosure	IP 65
Operating Temperature	-15 °C ~ +40 °C
Operating Temperature	-40 °C ~ +85°C
SAFETY	



Singel 3 | B-2550 Kontich | Belgium | Tel. +32 (0)3 458 30 33 | info@alcom.be | www.alcom.be

Rivium 1e straat 52 | 2909 LE Capelle aan den IJssel | The Netherlands | Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl

FSP TECHNOLOGY INC.



UL LISTED
I.T.E. POWER SUPPLY
E150014