NF21	12.2" Ruggedized Tablet
CPU	Kaby Lake U, i7 7600U
	Kaby Lake U, i5 7300U
os	Win10 x64
Display	12.2" 1920x1200 IPS 800 nits (Typ) sunlight readable
Touch Panel	10 pt.; gloves; water drop
GPU	Integrated with CPU
RAM	DDR4 8G SO-DIMM * 2, MAX support 16G
Storage	SSD: PCIE M.2 128GB
Front Camera	2MP: 1080P@30 fps/MJPEG, USB2.0 interface, light
Tiont Gamera	sensor (Win 10 Hello compatible)
Rear Camera	8MP: 1080P@30fps/MJPEG, Auto Foucs, Flash
	a/b/g/n/ AC 2.4G/5G 20M BW (Intel 8265 M.2 2X2 or
WLAN 802.11	Intel 3165)
	,
Bluetooth	BT 4.2 (Intel 8265 M.2 2X2)
GPS	Ublox NEO-M8N onboard
	Sierra EM7455 (EU & North America)
10/00 Barrie (antiqual)	- LTE FDD: Band B1-B5, B7, B12, B13, B17, B20,
4G/3G Bands (optional)	B25,B26, B29, B30, B41
	- UMTS/HSPA+: B1, B2, B3, B4, B5, B8
	2 x Digital microphone array (Win 10 Cortana)
Mic/Speaker	2 x 0.7W Sound pressure 70 db at 1.0M average at
	0.8KHz, 1.0KHz, 1.2Hz, and 1.5KHz.
	1 x Full size USB 3.0, (USB 2.0)
	1 x RJ45 LAN port
	1x DC jack Replaceable
	1 x Micro HDMI,
	1 x Headset 3.5mm (apple type)
	6 x Physical button (power, vol+, vol-, 1 x Barcode
I/O	scanner key, 2 programmable keys)
	1 x Reset hole
	1x Micro SIM
Sensors (type)	1x Micro SDXC card reader
	1xDocking POGO pin located at the bottom
	1xUSB 3.0 + USB 2.0 available in camera bay area
	Gyro
	Accelerometer
	E-compass
	Abient light
	Proximity
	•



	Finger Print (Win 10 Hello : optional)
Barcode Scanner (optional)	Honeywell N3680
RFID /NFC (optional)	Smart Approach SM-MSN10-C02
ТРМ	TPM 2.0
Battery (V & mAh)	Multiple packs; 7.6V x 6200 mAh standard battery / 47.12Wh
Backup Battery	142mAh Backup Battery / Hot swappable external battery for 60s
Work/Stand-By Hours	STD battery: up to 8 hours life time
LED	Power status LED: Off: Power off/Hibernation Green: Power on Blinking Green: Standby/Sleep Battery status LED: Green: Battery is fully charged Orange: Battery is charging, Blinking Orange: Battery capacity is lower than 7% HDD status LED: Green: when SSD is runing.
Stealth Mode	Single button press disables all following features: Speaker Screen backlight Indicator lights Radio transmitters (airplane mode)
Adaptor	120W (19.5V / 6.15A)
Security Feature	Kensington lock
Size (mm)	317.5(W)x214(H)x27.3(D)mm
Weight (gm)	1.9Kg
Operating Temp Range	-10°C to 50°C

ESD	8kV/15kV criteria C
Display Durability	Steel ball drop test, 25 mm diameter rounded end steel weight of 250 gm from 80cm. w/ screen proctector
Screen protector	Glass screen protector .4mm thickness with oleo phobic coating and anti-shatter laminate
Drop spec	4ft; MIL-STD-810G 26 times all corners and sides with single tablet while operating
Seal	IP65
Certifications Provided	FCC, CE,

Accessory Spec		
Office Dock (optional)	4x USB 3.0, Display Port, HDMI, VGA, RS232(w/5V output switch), Giga bit Ethernet, DC-in Jack, Audio In/Out, Kensington lock	
Vehicle Dock (optional)	Yes; Snap Mount MIL-STD-810G vibration at 10 times the power spectral density	

