

SIZE	OUTSIDE DIMENSIONS	SENSOR ACTIVE AREA	INTERFACE	COVER LENS THICKNESS	Color	PART NUMBER
7"W	166.49 x 100 mm	Max: 157.1 x 89.1 mm	COF Combo USB/I2C	0.7 mm	CS Transparent	RTPC070WF1-R07TG1-C
	161.86 x 103.57 mm	Max: 154.7 x 93.77 mm	COF Combo USB/I2C	0.7 mm	CS Transparent	RTPC070W-R07TG1-C
	193 x 136 mm	153.4 x 92.4 mm	COF Combo USB/I2C	3 mm	Black PMMA	RTPC070W-R30BP1-C
	193 x 136 mm	154.1 x 90.5 mm	COF Combo USB/I2C	3 mm	Black PMMA	RTPC070W-R30003-C
8.4"	183.7 x 143.4 mm	Max: 174.4 x 131.8 mm	COF USB/I2C	1.1 mm	CS Transparent	RTPC084-S11TG1 (U/I)
	222.4 x 165.8 mm	171.0 x 128.4 mm	COF USB/I2C	1.8 mm	Black PMMA	RTPC084-S18BP1 (U/I)
10.0"W	236.22*143.69 mm	Max: 225.02 x 127.59 mm	E-COF Combo USB/I2C	1.1 mm	CS Transparent	RTPC100WF1-R1-11TG1-C
	263.2 x 165.9 mm	223.32*125.88 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC100WF1-R1-30BP1-C
	263.2 x 165.9 mm	223.32*125.88 mm	E-COF Combo USB/I2C	6 mm	Black Ceramic	RTPC100WF1-R1-60BC1-C
10.1"W	232 x 156.7 mm	Max: 218.96 x 137.7 mm	E-COF Combo USB/I2C	1.1 mm	CS Transparent	RTPC101WF1-R1-11TG1-C
	254.96 x 172.6 mm	217.96 x 136.6 mm	E-COF Combo USB/I2C	1.1 mm	Black PMMA	RTPC101WF1-R1-11BP1-C
	254.96 x 172.6 mm	217.96 x 136.6 mm	E-COF Combo USB/I2C	3.2 mm	Black Ceramic	RTPC101WF1-R1-32002-C
	283 x 202 mm	217.96 x 136.6 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC101WF1-R1-30BP1-C
10.4"	230.7 x 174.6	212.6 x 161 mm	COF USB/I2C	1.1 mm	CS Transparent	RTPC104H11001 (U/I)
	233.9 x 187.9 mm	Max: 221.49 x 168.46 mm	E-COF Combo USB/I2C	1.1 mm	CS Transparent	RTPC104F1-R1-11TG1-C
	280 x 227 mm	212.2 x 159.4 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC104F1-R1-30BP1-C
12.1"	271.3 x 213.6 mm	Max: 255 x 193.5 mm	E-COF Combo USB/I2C	1.1 mm	CS Transparent	RTPC121F1-R1-11TG1-C
	315 x 253 mm	247.0 x 185.5 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC121F1-R1-30BP1-C
				6 mm	Black Ceramic	RTPC121F1-R1-60BC1-C
12.1"W	285 x 186.8 mm	Max: 269 x 166.92 mm	E-COF Combo USB/I2C	1.1 mm	CS Transparent	RTPC121WF1-R1-11TG1-C
	328 x 226 mm	262.12 x 164.2 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC121WF1-R1-30BP1-C
				6 mm	Black Ceramic	RTPC121WF1-R1-60BC1-C
12.3"W Cut	322.4 x 142.1 mm	293.2 x 110.7 mm	COF Combo USB/I2C	1.8 mm	Black PMMA	RTPC123W-R18BP1-C
15"	324.2 x 256.8 mm	Max 308.13 x 232.02 mm	E-COF Combo USB/I2C	1.1 mm	CS Transparent	RTPC150F1-R1-11TG1-C
	346.5 x 275 mm	305.1 x 229.1 mm	E-COF Combo USB/I2C	1.8mm	Black PMMA	RTPC150F1-R1-18001-C
	370.1 x 294.1 mm	305.1 x 229.1 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC150F1-R1-30BP1-C
15.6"W	370.3 x 222.2 mm	Max: 346.33 x 195.94 mm	E-COF Combo USB/I2C	1.1 mm	CS Transparent	RTPC156WF1-R1-11TG1-C
	424 x 273 mm	345.23 x 194.54 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC156WF1-R1-30BP1-C
				6 mm	Black Ceramic	RTPC156WF1-R1-60BC1-C
17"	393.8 x 243.8 mm	345.23 x 194.54 mm	E-COF Combo USB/I2C	6 mm	Black Ceramic	RTPC156WF1-R1-60002-C
	370 x 301.7 mm	Max: 348.2 x 280.88 mm	E-COF Combo USB/I2C	1.8 mm	CS Transparent	RTPC170F1-R1-18TG1-C
	424 x 357 mm	338.92 x 271.33 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC170F1-R1-30BP1-C
18.5"W				6 mm	Black Ceramic	RTPC170F1-R1-60BC1-C
	440.6 x 261.6 mm	Max: 411.8 x 232.4 mm	E-COF Combo USB/I2C	1.8 mm	CS Transparent	RTPC185WF1-R1-18TG1-C
	491 x 312 mm	410.8 x 231.4 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC185WF1-R1-30BP1-C
19"				6 mm	Black Ceramic	RTPC185WF1-R1-60BC1-C
	411.1 x 332.4 mm	Max: 386.65 x 311.52 mm	E-COF Combo USB/I2C	1.8 mm	CS Transparent	RTPC190F1-R1-18TG1-C
	457.32 x 382.06 mm	377.32 x 302.06 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC190F1-R1-30BP1-C
19.2"W Cut				6 mm	Black Ceramic	RTPC190F1-R1-60BC1-C
	513 x 127 mm	478 x 89.5 mm	COF Combo USB/I2C	3.2mm	Black Ceramic	RTPC192W-R32BC1-C
	432 x 331.5 mm	Max: 409.6 x 307.6 mm	E-COF Combo USB/I2C	3mm	CS Transparent	RTPC201F1-R1-30001-C
20.1"	432 x 331.5 mm	408.6 x 306.6 mm	E-COF Combo USB/I2C	3mm	Black PMMA	RTPC201F1-R1-30002-C
	507.1 x 298.7 mm	Max: 479 x 270.5 mm	E-COF Combo USB/I2C	1.8 mm	CS Transparent	RTPC215WF1-R1-18TG1-C
	520.64 x 312.11	477.84 x 269.31	E-COF Combo USB/I2C	3mm	Black PMMA	RTPC215WF1-R1-30001-C
21.5"W				3 mm	Black PMMA	RTPC215WF1-R1-30BP1-C
	559 x 350 mm	477.64 x 269.11 mm	E-COF Combo USB/I2C	6 mm	Black Ceramic	RTPC215WF1-R1-60BC1-C
	558.64*321.86 mm	Max: 527.64 x 297.06 mm	E-COF Combo USB/I2C	1.8 mm	CS Transparent	RTPC238WF1-R1-18TG1-C
23.8"W/23.6"W	576.64*346.06 mm	526.64 x 296.06 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC238WF1-R1-30BP1-C
				6 mm	Black Ceramic	RTPC238WF1-R1-60BC1-C
24"W	551 x 350.4 mm	Max: 519.98 x 325.6 mm	E-COF Combo USB/I2C	1.8mm	CS Transparent	RTPC240WF1-R1-18TG1-C
27.0"W	613.89*362.11 mm	Max: 599.89 x 338.31 mm	E-COF Combo USB/I2C	1.8 mm	CS Transparent	RTPC270WF1-R1-18TG1-C
	644.2 X 388.4 mm	598.4 x 337.0 mm	E-COF Combo USB/I2C	3 mm	Black PMMA	RTPC270WF1-R1-30BP1-C
31.5"W				6 mm	Black Ceramic	RTPC270WF1-R1-60BC1-C
	507.1 x 298.7 mm	Max: 486.78 x 276.96 mm	External Controller (USB/RS232)	1.8 mm	CS Transparent	RTPC315W-S18TG1