




Product Specification				
	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	1 / 16

**Thin-Film-Transistor LCD Module  
Model: GATC14TNJD1E0**


Acceptance

**Solomon Goldentek Display Corp.**  
**NO. 18 Ta-Yeh St., Ta-Fa Industrial Park, Ta-Liao**  
**Hsiang, Kaohsiung Hsien 831, TAIWAN , R.O.C.**  
**FAX: 886-7-7886800**

Approved and Checked by

Approved by	Checked by		Made by
			

## Product Specification


	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	2 / 16

### Revise Records

Rev.	Date	Contents	Written	Approved
A	2019/04/22	Preliminary Specification	Roy	LF

### Special Notes


Note1.	
Note2.	
Note3.	
Note4.	
Note5.	

Product Specification				
	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	3 / 16

## Contents

<b>1. General Description and Features.....</b>	<b>4</b>
1.1. Features	4
1.2. LCD Module	4
<b>2. Mechanical Information.....</b>	<b>4</b>
<b>3. Electrical Specifications .....</b>	<b>5</b>
3.1 Absolute Max. Ratings	5
<b>4. Electrical Characteristics.....</b>	<b>6</b>
4.1. TFT-LCD Module	6
4.2. Backlight Unit	6
<b>5. Input Terminal Pin Assignment .....</b>	<b>7</b>
5.1. Pin Assignment (LCD)	7
<b>6. Optical Characteristics .....</b>	<b>8</b>
<b>7. Reliability Condition.....</b>	<b>11</b>
<b>8. DIMANSIONAL OUTLINE.....</b>	<b>12</b>
<b>9. Incoming Inspection Standards .....</b>	<b>13</b>
9.1. Inspection and Environment Conditions	13

## Product Specification

	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	4 / 16

### 1. General Description and Features

GATC14NNJD1E0 is a color active matrix LCD module incorporating amorphous silicon TFT (Thin Film Transistor). It is composed of a color TFT-LCD panel, driver IC, FPC and a back light unit. The module display area contains 128x128 pixels and can display up to 262K colors.

#### 1.1. Features

- 128 x 128 pixels resolution.
- Display in 262K colors
- MCU Bit system interface
- RoHS Compliance

#### 1.2. LCD Module

Item	Specification	Unit
Screen Size	1.44 inches	Diagonal
Display Resolution	128 x RGB x 128	Dot
Active Area	25.4976(H) x 26.496(V)	mm
Outline Dimension	29.0(H) x 34.69(V) x 2.6(T)	mm
Display Mode	Normally white, TN/Transmissive	--
Pixel Arrangement	RGB Vertical stripes	--
Pixel Pitch	0.1992(H) × 0.207 (V)	mm
Surface Treatment	Anti-Glare	--
Display Color	262K	--
Viewing Direction	12 o'clock	--
Input Interface	MCU	--


### 2. Mechanical Information

Item	Min.	Typ.	Max.	Unit	Note	
Module Size	Horizontal (H)	28.8	29.0	29.2	mm	--
	Vertical (V)	34.49	34.69	34.89	mm	
	Thickness (T)	2.5	2.6	2.7	mm	(1)
Weight	--	TBD	--	g	--	

Note (1) Not include Component.

Refer to the Outline Dimension for further information.

## Product Specification

	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	5 / 16

### 3. Electrical Specifications

#### 3.1 Absolute Max. Ratings

##### 3.1.1 Absolute Ratings of Environment

If the operating condition exceeds the following absolute maximum ratings, the TFT LCD module may be damaged permanently.

(Ta=25±2°C, V<sub>SS</sub>=GND=0)

Item	Symbol	Min.	Max.	Unit	Note
Storage temperature	T <sub>STG</sub>	-30	85	°C	(1)
Operating temperature	T <sub>OPR</sub>	-30	85	°C	(1,2,3)

Note (1) 90 % RH Max. ( 40 °C ≥ Ta ). Maximum wet-bulb temperature at 39 °C or less. (Ta > 40 °C) No condensation.

Note (2) In case of below 0°, the response time of liquid crystal (LC) becomes slower and the color of panel becomes darker than normal one. Level of retardation depends on temperature, because of LC's character

Note (3) Only operation is guaranteed at operating temperature. Contrast, response time, another display quality are evaluated at +25°C.


#### 3.2 Electrical Absolute Rating

The following are maximum values which, if exceeded, may cause faulty operation or damage to the unit.

(V<sub>SS</sub>=GND=0)

Item	Symbol	Min.	Max.	Unit	Note
Logic power supply	V <sub>DD</sub>	-0.3	+4.6	V	
Logic input voltage	V <sub>IN</sub>	-0.3	V <sub>DD</sub> +0.3	V	
Power Supply Current	I <sub>CC</sub>	-	TBD	mA	

## Product Specification

	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	6 / 16

### 4. Electrical Characteristics

#### 4.1. TFT-LCD Module


ITEM	SYMBOL	MIN	TYP	MAX	UNIT	NOTE
Power supply of IO pins	$V_{DD}$	1.65	1.8	3.7	V	
Input voltage	$V_{IH}$	$0.7V_{DD}$	-	$V_{DD}$	V	
	$V_{IL}$	$V_{SS}$	-	$0.3V_{DD}$	V	
Power supply current	$I_{DD}$		TBD		$\mu A$	

#### 4.2. Backlight Unit

( $T_a=25\pm 2^\circ C$ )

Item	Symbol	Value			Unit	Note
		Min.	Typ.	Max.		
LED Total Input Voltage	$V_L$	2.8	3	3.2	V	
LED Total Input Current	$I_L$	-	20	-	mA	(1)
Power Consumption	$P_{BL}$	-	60	64	mW	(2)
Life time	-	50,000	-	-	Hrs	(3)


Note (1) Circuit diagram



(2) Where  $I_L = 20mA$ ,  $V_L = 3$ ,  $P_{BL} = V_L \times I_L$

(3) The environmental conducted under ambient air flow ,at  $T_a=25\pm 2^\circ C$ , 60%RH $\pm 5\%$

## Product Specification


	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	7 / 16

### 5. Input Terminal Pin Assignment

#### 5.1. Pin Assignment (LCD)

Pin No.	Symbol	Function	Remark
1	NC	NOT connect	
2	GND	Ground	
3	GND	Ground	
4	TE	Tearing effect output	
5	/RESET	RESET SIGNAL	
6	VCI	Power Supply for LCD	
7	VCI	Power Supply for LCD	
8	VCC	Power Supply for LCD(1.8V/2.8V)	
9	NC	NOT connect	
10	GND	Ground	
11	NC	NOT connect	
12	LEDA	LED backlight anode	
13	NC	NOT connect	
14	LEDK	LED backlight cathode	
15	GND	Ground	
16	NC	NOT connect	
17	DB7	Databus	
18	DB6	Databus	
19	DB5	Databus	
20	DB4	Databus	
21	DB3	Databus	
22	DB2	Databus	
23	DB1	Databus	
24	DB0	Databus	
25	GND	Ground	
26	WR	Write signal	
27	RS	Register Select Signal	
28	CS	Chip select	
29	RD	Read Signal and Read Data	

## Product Specification

	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	8 / 16

30	GND	Ground	
31	GND	Ground	
32	VPP	NC	

### 6. Optical Characteristics

Item	Symbol	Condition	Min	Type	Max	Unit	Note	
Brightness	B		96	120	-	cd/m <sup>2</sup>		
Response Time (White - Black)	Tr + Tf	$\theta=0^\circ$	-	25	-	ms		
Contrast ratio	CR	At optimized viewing angle	-	350	-	--		
Luminance Uniformity	$\Delta L$		80	85		%		
Color Chromaticity (CIE 1931)	White	Wx	$\theta=0^\circ$ Normal Viewing Angle	0.273	0.313	0.353	--	BM-7A
		Wy		0.289	0.329	0.369		
Viewing Angle	Ver.	$\theta_U$	CR $\geq$ 10	-	35	--	Degree	
		$\theta_D$		-	15	--		
	Hor.	$\theta_R$		-	45	--		
		$\theta_L$		-	45	--		

a. Test equipment setup

After stabilizing and leaving the panel alone shall be warmed up for the stable operation of LCM, the measurement should be executed. Measurement should be executed in a stable, windless, and dark room. Optical specifications are measured by Topcon BM-7(fast) with a viewing angle of 1° at a distance of 50cm and normal direction.

b. Definition of response time: Tr and Tf

The response time is defined as the following figure and shall be measured by switching the input signal for "black" and "white".



## Product Specification



Model: GATC14TNJD1E0

Rev. No.


Issued Date.

Page.

A

2019/04/22

9 / 16




c. Definition of contrast ratio:


$$\text{Contrast Ratio (CR)} = \frac{\text{Brightness measured when LCD is at "white state"}}{\text{Brightness measured when LCD is at "black state"}}$$

d. Measured at the center area of the panel when all the input terminals of LCD panel are electrically opened.

e. View Angle



## Product Specification

	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	10 / 16

f. Definition of Luminance of White: Luminance of white at the center points

Light Source of Back-Light Unit	LED Type
---------------------------------	----------


g. Definition of White Uniformity

$$\text{White Uniformity} = \frac{\text{Min. luminance of white among 9-points}}{\text{Max. luminance of white among 9-points}} \times 100\%$$


h. The definition of Color Gamut -Color Chromaticity CIE 1931

Color coordinate of white & red, green, blue at center point.

Color Gamut : NTSC(%) = ( RGB Triangle Area / NTSC Triangle Area ) x 100



## Product Specification

	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	11 / 16

### 7. Reliability Condition


No change on display and in operation under the following test condition.

Condition: Unless otherwise specified, tests will be conducted under the following condition.

Temperature:  $20 \pm 5^\circ\text{C}$ .

Humidity:  $65 \pm 5\% \text{RH}$ .

Tests will be not conducted under functioning state.

No.	Parameter	Condition	Notes
1	High Temperature Operating	$85^\circ\text{C} \pm 2^\circ\text{C}$ , 120hrs (Operation state).	
2	Low Temperature Operating	$-30^\circ\text{C} \pm 2^\circ\text{C}$ , 120hrs (Operation state).	1
3	High Temperature Storage	$85^\circ\text{C} \pm 2^\circ\text{C}$ , 120hrs.	2
4	Low Temperature Storage	$-30^\circ\text{C} \pm 2^\circ\text{C}$ , 120hrs.	1,2
5	High Temperature and High Humidity Operation Test	$60^\circ\text{C} \pm 2^\circ\text{C}$ , 90%, 120hrs.	1,2
6	Vibration Test	Total fixed amplitude: 1.5mm. Vibration Frequency: 10~55Hz. One cycle 60 seconds to 3 direction of X, Y, Z each 15 minutes.	3
7.	Drop Test	To be measured after dropping from 60cm high on the concrete surface in packing state.  	<p style="color: blue;"><i>Dropping method corner dropping:</i></p> <p style="color: blue;"><i>A corner: Once edge dropping.</i></p> <p style="color: blue;"><i>B, C, D edge: Once face dropping.</i></p> <p style="color: blue;"><i>E, F, G face: Once.</i></p>

- Notes:
1. No dew condensation to be observed.
  2. The function test shall be conducted after 4 hours storage at the normal temperature and humidity after removed from the test chamber.
  3. Vibration test will be conducted to the product itself without putting I in a container.

# Product Specification



Model: GATC14TNJD1E0

Rev. No.

Issued Date.


Page.

A


2019/04/22

12 / 16

## 8. DIMANSIONAL OUTLINE



## Product Specification


	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	13 / 16

### 9. Incoming Inspection Standards

#### 9.1. Inspection and Environment Conditions

##### 9.1.1. Inspection Conditions:

- (1) Inspection Distance: 35 cm±5cm
- (2) View Angle : Light-on Inspection Angle : ±5°  
Cosmetic Inspection Angle : ±45°



( perpendicular to LCD panel surface)

##### 9.1.2. Environment Conditions:

Ambient Temperature		23°C±5°C
Ambient Humidity		55±10%RH
Ambient Illumination	Cosmetic Inspection	more than 600 Lux
	Functional Inspection	300~500 Lux


##### 9.1.3. Sampling Conditions:

- (1) Lot Size: Quantity of shipment lot per model
- (2) Sampling Method:

Sampling Plan		MIL-STD-105E
		Normal Inspection, Single Sampling
		Level II
AQL	Major Defect	1.0%
	Minor Defect	1.5%



- (3) The classification of Major(MA) and Minor(MI) defects is shown as 3. Inspection Criteria.


## Product Specification

	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	14 / 16

### 9.1.4. Inspection Criteria

#### 9.1.4.1. Cosmetic Inspection(Panel):

Item	Judgment Criteria	Classification
Chipping on Panel	 <p style="text-align: center;"><math>a \leq 3.0\text{mm}</math>, <math>b \leq 3.0\text{mm}</math>, <math>c \leq t</math> ( Bottom glass thickness)</p>	MA
Scratch on Panel *Note-2	<p style="text-align: center;"><math>W \leq 0.05\text{mm}</math> or <math>L &lt; 5\text{mm}</math>: Ignored</p> <p style="text-align: center;"><math>0.05\text{mm} &lt; W \leq 0.1\text{mm}</math> and <math>L \leq 5\text{mm}</math>: <math>N \leq 5</math></p> <p style="text-align: center;"><math>W &gt; 0.1\text{mm}</math> or <math>L &gt; 5\text{mm}</math>: Not allowed</p>	MI
Bubble or Dent on Panel *Note-3	<p style="text-align: center;"><math>D \leq 0.2\text{mm}</math>: Ignored</p> <p style="text-align: center;"><math>0.2\text{mm} &lt; D \leq 0.3\text{mm}</math>: <math>N \leq 5</math></p> <p style="text-align: center;"><math>D &gt; 0.3\text{mm}</math>: Not allowed</p>	MI
Panel Crack	 <p style="text-align: center;">Not Allowed crack</p>	MA
Bezel Deformation	Obvious deformation is not allowed.	MI
Bezel Oxidation	Not allowed if it rusts continuously over 1 cm (It is out of warranty with rusted tin plate)	MI
Bezel Scratch	$L \leq 20\text{mm}$ , $W \leq 0.2$ , $N \leq 3$	MI
Metal Squash Dent /Flange(Front Side)	$D(W) \leq 1, L \leq 3, N \leq 3;$	MI
B/L High Voltage Wire Denudation	Not allowed	MA
Polarizer flaw or leak out resin	Defect is defined as the active area.	MI


Product Specification				
	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	15 / 16

Outline Dimension	Must in Spec, refer to related product spec.	MI
-------------------	--	----


9.1.4.2. Functional Inspection:

Item	Judgment Criteria			Classification
	Area(Note1)	I	O	
Point Defect	Bright dot	Random	1	
		2 dots adjacent	0	0
		3 dots adjacent or more	0	0
	Dark dot	Random	2	
		2 dots adjacent	0	
		3 dots adjacent or more	0	0
	Total Dot Defect		3	
	Distance	Distance between Bright and Bright dot	$L \geq 5\text{mm}$	
		Distance between Bright and Dark dot	$L \geq 5\text{mm}$	
		Distance between Dark dot	$L \geq 5\text{mm}$	
(1) It is defined as Point Defect if defect area $> 0.5\text{dot}$ (2) It is ignored if defect area $\leq 0.5\text{dot}$ (3) Weak point defect will be defined as Bright Dot if it can be observed through ND filter 5%( Full Screen Black Inspection)				
Line Defect	Obvious vertical or horizontal line defect is not allowed.			MA
Mura	Not allowed if it can be observed through ND Filter 5 %			MI
Foreign Material in spot shape *Note-3	$D \leq 0.2\text{mm}$ : Ignored $0.2\text{mm} < D \leq 0.3\text{mm}$ : $N \leq 3$ $D > 0.3\text{mm}$ : Not allowed			MI
Foreign Material in line or spiral shape *Note-4	$W \leq 0.05\text{mm}$ or $L \leq 3\text{mm}$ : Ignored $0.05\text{mm} < W \leq 0.1\text{mm}$ and $1.0\text{mm} < L \leq 2\text{mm}$ : $N \leq 4$ $W > 0.1\text{mm}$ or $L > 5\text{mm}$ : Not allowed			MI
Display Function Abnormal	No Malfunction can be allowed			MA


## Product Specification

	Model: GATC14TNJD1E0	Rev. No.	Issued Date.	Page.
		A	2019/04/22	16 / 16


Note-1 : I/O Area Definition



Note-2 : Polarizer Scratch



Note-3 : Spot Foreign Material  
( $W \geq L / 4$ )



Note-4 : Line or Spiral Foreign Material  
( $W < L / 4$ )

