



Product Name: PB50DMX Castle Patch Antenna

Part Number: H2P13648210100

Features:

- Supporting: (L1+L2) GPS/GLONASS/BDS/Galileo/QZSS
- Dimensions: 50 x 50 x 8mm
- Stable and reliable in performances
- Low temperature coefficient of frequency
- RoHS 2.0 compliance

Applications:

- Automotive telematics
- Safety of life transportation
- Marine
- Navigation

Castle Patch Antenna-508-2pins

MODEL: PB50DMX

Version: A


I. Patch Antenna Specifications:

Items	Specifications	
Navigation	GPS L1/ GLONASS G1/ Galileo E1/ BDS B1/ QZSS L1	GPS L2/ GLONASS G2/ QZSS L2
Center Frequency (MHz)	1575.42	1227.6
Peak Gain(dBi)	4.5 Typ.	6.2 Typ.
Return loss (dB)	< -10 Typ.	
Axial Ratio (dB)	< 3 Typ.	
Average Gain(dB)	-3.0 Typ.	-1.2 Typ.
Efficiency (%)	53 Typ.	78 Typ.
Test Condition	100 x 100 mm ² (Evaluation board)	
Impedance(Ω)	50	
Polarization	RHCP	

Mechanical Specifications	
Dimensions (mm)	50(L) x 50 (W) x8 (H)
Material	Ceramic
Environmental Conditions	
Operation Temperature (°C)	-40 ~ +85
Storage Temperature (°C)	-5 ~ +40
Relative Humidity	10 ~ 70 %

© Unictron Technologies Corp.
All specifications subject to change without notice.

II. Antenna Dimensions (unit: mm):





© Unictron Technologies Corp.
All specifications subject to change without notice.

NOTE:

1. All materials are RoHS 2.0 compliant.
2. "A~E" Critical Dimensions.
3. "()" Reference Dimensions.


III. Block Diagram




IV. Properties:

a) Return loss (dB)

I. GNSS L1 Band (with coupler)




II. GNSS L2 Band (with coupler)




© Unictron Technologies Corp.
All specifications subject to change without notice.

b) Peak Gain vs. Frequency (with coupler)

I. GNSS L1 Band




II. GNSS L2 Band




© Unictron Technologies Corp.
All specifications subject to change without notice.

c) Axial vs. Frequency (with coupler)

I. GNSS L1 Band




II. GNSS L2 Band




© Unictron Technologies Corp.
All specifications subject to change without notice.

d) Average Gain(dB) (with coupler)

I. GNSS L1 Band




II. GNSS L2 Band




© Unictron Technologies Corp.
All specifications subject to change without notice.

e) Efficiency (%) (with coupler)

I. GNSS L1 Band




II. GNSS L2 Band



© Unictron Technologies Corp.
All specifications subject to change without notice.


V. Antenna Radiation Pattern Measurement:

The antenna radiation patterns are measured in Unictron's 3D Anechoic Chamber. The measurement setup is as show below.




© Unictron Technologies Corp.
All specifications subject to change without notice.


2D Radiation Gain Pattern



a) GNSS L1 Band @1575.42MHz (unit: dBi)



b) GNSS L2 Band @1227.6MHz (unit: dBi)







© Unictron Technologies Corp.
All specifications subject to change without notice.

VI. Packing:

- a) Weight:
Unit Weight: 38.8 ± 4 (g)
- b) Quantity:
Each Vacuum Bag: 150 pcs
Each Outer Box: 150 pcs

© Unictron Technologies Corp.
All specifications subject to change without notice.

Step	Pictures	Descriptions
1		Place three trays into one stack. Once stacked, place a sheet of EPE in the depression on the top tray, and then another tray on top. Place another sheet of EPE beneath the bottom tray to complete the stack. Make sure the trays and the EPE sheets are lined up correctly.
2		Place the stacked trays on the packaging machine to be tape punched and tightly secured.
3		Place the stacked trays into a vacuum bag to be vacuum sealed, and then labeled.
4		Place one vacuum bags vertically into a carton and then seal the carton.