

Specification

| | | |
|--------------|---|---|
| Part No. | : | WSA.2458.A.101151 |
| Product Name | : | Phoenix WSA.2458 Dual Band Wi-Fi I-Bar 2.4/5.8GHz Antenna with 1M RG-174 RP-SMA(M) |
| Feature | : | Wi-Fi/WLAN Adhesive Mount Antenna 1m RG-174 cable with RP-SMA(M) connector Low Profile for Ease of Installation Fully Customizable Cable and Connector 105*30*7.7mm RoHS compliant |



1. Introduction

The Phoenix WSA.2458 I-Bar antenna is a robust and low profile, dipole antenna operating on both the 2.4/5.8GHz bands for Wi-Fi applications.

The Phoenix has a slim-line design, which allows for covert and convenient installation in any application, while its omnidirectional radiation pattern and 2.1dBi gain ensure constant reception and transmission. It is manufactured and tested in a TS16949 first tier automotive approved facility and has undergone full PPAP design, reliability and quality audits.

The Phoenix is especially suited for applications such as first-tier automotive applications, aftermarket and telematics.

The Phoenix has exceptional industry performance characteristics considering its very low profile (just 7.7mm) and compact size (105*30mm).

This UV resistant antenna is designed to be mounted on glass or plastic but should not be mounted on a metal base. It comes with strong 3M double-sided adhesive for a permanent and secure fix to your application.

Cable lengths, types and connectors are fully customizable.

2. Specification


| Wi-Fi | | | |
|-------------------|------|--------------|--------------|
| Frequency | | 2400~2500MHz | 4900~5850MHz |
| Efficiency (%) | | | |
| In free space | 0.3m | 68.23 | 47.03 |
| | 1m | 54.10 | 33.08 |
| | 2m | 38.61 | 20.16 |
| | 3m | 27.62 | 12.13 |
| | 5m | 14.32 | 4.45 |
| On glass | 0.3m | 70.19 | 40.72 |
| | 1m | 55.64 | 28.64 |
| | 2m | 39.72 | 17.47 |
| | 3m | 28.42 | 10.51 |
| | 5m | 14.73 | 3.86 |
| On the 2mm ABS | 0.3m | 69.94 | 46.77 |
| | 1m | 55.43 | 32.90 |
| | 2m | 39.58 | 20.05 |
| | 3m | 28.31 | 12.06 |
| | 5m | 14.67 | 4.43 |
| Average Gain(dBi) | | | |
| In free space | 0.3m | -1.66 | -3.30 |
| | 1m | -2.67 | -4.84 |
| | 2m | -4.13 | -7.00 |
| | 3m | -5.59 | -9.22 |
| | 5m | -8.44 | -13.59 |
| On glass | 0.3m | -1.54 | -3.94 |
| | 1m | -2.55 | -5.48 |
| | 2m | -4.01 | -7.64 |
| | 3m | -5.46 | -9.86 |
| | 5m | -8.32 | -14.23 |
| On the 2mm ABS | 0.3m | -1.55 | -3.33 |
| | 1m | -2.56 | -4.86 |
| | 2m | -4.03 | -7.02 |
| | 3m | -5.48 | -9.24 |
| | 5m | -8.33 | -13.62 |




| Peak Gain(dBi) | | | |
|----------------------|-----------------|-------|-------|
| In free space | 0.3m | 2.65 | 3.19 |
| | 1m | 1.55 | 1.73 |
| | 2m | 0.15 | -0.31 |
| | 3m | -1.35 | -2.41 |
| | 5m | -4.25 | -6.61 |
| On glass | 0.3m | 3.98 | 4.22 |
| | 1m | 2.89 | 2.72 |
| | 2m | 1.48 | 0.62 |
| | 3m | -0.02 | -1.58 |
| | 5m | -2.89 | -5.88 |
| On the 2mm ABS | 0.3m | 2.95 | 4.31 |
| | 1m | 1.89 | 2.81 |
| | 2m | 0.45 | 0.81 |
| | 3m | -1.05 | -1.29 |
| | 5m | -3.91 | -5.49 |
| Return loss | < -10 dB | | |
| VSWR | ≤ 2:1 | | |
| Impedance | 50Ω | | |
| Polarization | Linear | | |
| Radiation Pattern | Omnidirectional | | |
| Input Power | 2W | | |
| MECHANICAL | | | |
| Dimensions | 105*30*7.7mm | | |
| Casing | PC/ABS | | |
| Connector | RP-SMA(M) | | |
| Cable | RG-174 | | |
| Weight | 50g | | |
| ENVIRONMENTAL | | | |
| Temperature Range | -40°C to 85°C | | |

3. Antenna Characteristics


3.1 Antenna Test Setup



Free Space




On Glass




On 2mm ABS



3.2 Return Loss




3.3 Efficiency






3.4 Peak Gain




3.5 Average Gain






4 Antenna Radiation Patterns


4.1 Antenna setup (Free space with 1 meter cable length)



Free Space



On Glass



On 2mm ABS



Antenna testing Setup in ETS Anechoic Chamber



4.2 2D Radiation Patterns



4.2.1 Free Space

XY Plane







XZ Plane







YZ Plane







4.2.2 On Glass

XY Plane







XZ Plane





TAOGLAS®



YZ Plane







4.2.3 On 2mm ABS

XY Plane







XZ Plane






YZ Plane






4.3 Antenna 3D Radiation Pattern

4.3.1 Free Space




2450MHz




5550MHz



4.3.2 On Glass




2450MHz




5550MHz



4.3.3 On 2mm ABS




2450MHz



5550MHz



5 Drawing (Unit: mm)



| | Name | P/N | Material | Finish | QTY |
|---|-----------------------|----------------|----------|------------|-----|
| 1 | Housing | 000112G000015A | PC+ABS | Black | 1 |
| 2 | Double Sided Adhesive | 001011J000015A | 3M 1600T | Blue Liner | 1 |
| 3 | 2.4/5.8 GHz Label | 001016G070000A | PEPA | Teal Green | 1 |
| 4 | Heat Shrink Tube | 001315C020000A | PE | Black | 1 |
| 5 | RG174 Coaxial Cable | 301315C000000A | PVC | Black | 1 |
| 6 | RP-SMA(M) | 200214E000015A | Brass | Au Plated | 1 |




6 Packaging


WSA.2458.A.101151

Packaging Specifications


1pcs WSA.2458.A.101151 per PE Bag
Bag Dimensions - 190 x 70mm
Weight - 34.5g



200 pcs WSA.2458.A.101151 per carton
Carton - 400x 330 x 220mm
Weight - 7.1Kg



Pallet Dimensions 120 x 110x 150cm
54 Cartons per Pallet
9 Cartons per layer
6 Layers






7 Application Note


The WSA.2458 antenna performance with different cable lengths is shown below.

7.1 In free Space

Return Loss




Efficiency






Peak Gain




Average Gain






7.2 On Glass

Return Loss




Efficiency






Peak Gain




Average Gain






7.3 On 2mm ABS

Return Loss




Efficiency





Peak Gain



Average Gain

