

AC-DC ITE Power Module

■ = New Model, ■ = Current Model, ■ = Not Recommended for New Designs

Output Power	Series	Picture	Circuit	I/P Voltage Range (V.AC)	Output Voltage Range (V.DC)	Isolation Voltage (V.AC)	Operating Temperature	Dimensions (mm)	Warranty
2W	AYC		Class II	90~305	Single 3.3 · 5 · 9 · 12 · 15 · 24	3000	-40°C~80°C	33.7 x 22.2 x 17.0 CE RoHS CB	3-Year
	AZC		Class II	90~305	Single 3.3 · 5 · 9 · 12 · 15 · 24	3000	-40°C~80°C	28.8 x 26.1 x 17.3 CE RoHS CB	3-Year
3W	AIC		Class II	90~264	Single 3.3 · 5 · 9 · 12 · 15 · 24	3750	-40°C~85°C	35.7 x 19.0 x 22.0 CE RoHS CB	3-Year
4W	AOC		Class II	90~264 and 90~305	Single 3.3 · 5 · 8 · 9 · 12 · 14 · 15 · 24	3000	-40°C~70°C	37.0 x 27.5 x 17.5 CE RoHS CB	3-Year
	AOCH	Dual 5/3.3 · 8/5 · 12/5							
5W	AHCH05		Class II	90~305	Single 3.3 · 5 · 12 · 24	4000	-40°C~85°C	51.82 x 26.42 x 16.51 CE RoHS CB	3-Year
	AOCH05		Class II	90~305	Single 3.3 · 5 · 12 · 24	4000	-40°C~70°C	37.0 x 27.5 x 17.5 CE RoHS CB	3-Year
7W	AUC		Class II	90~264	Single 5 · 12 · 15 · 24	3000	-40°C~70°C	27.4 x 27.4 x 18.7 CE RoHS CB	3-Year
8W	AHC08		Class II	90~305	Single 3.3 · 3.8 · 5 · 8 · 9 · 12 · 14 · 15 · 24	3000	-40°C~70°C	52.2 x 26.8 x 19.0 CE RoHS	3-Year
	ALC	Dual 5/3.3 · 8/5 · 12/5 · 12/7.5							
10W	AHCH10		Class II	90~305	Single 5 · 12 · 15 · 24	4000	-40°C~85°C	52.2 x 26.8 x 19.0 CE RoHS CB	3-Year
	AOCH10		Class II	90~305	Single 5 · 12 · 15 · 24	4000	-40°C~70°C	37.0 x 27.5 x 20.0 CE RoHS CB	3-Year
	AOD10		Class II	90~264	Single 5 · 12 · 15 · 24	3000	-40°C~70°C	37.0 x 27.5 x 20.0 CE RoHS CB	3-Year
15W	AVC		Class II	90~264	Single 5 · 12 · 15 · 24	4000	-40°C~70°C	41.2 x 27.2 x 19.1 CE RoHS CB	3-Year
	APCN		Class II	90~264	Single 5 · 12 · 15 · 24	4000	-40°C~70°C	54.7 x 44.9 x 21.0 CE RoHS CB	3-Year
	ATCN		Class II	90~264	Single 5 · 12 · 15 · 24	4000	-40°C~70°C	64.3 x 45.1 x 21.7 CE RoHS CB	3-Year
	MFC15		Class II	90~264	Single 5 · 9 · 12 · 15 · 24	4000	-40°C~80°C	52.5 x 27.5 x 23.5 CE RoHS CB	3-Year
20W	AFC20		Class II	90~264	Single 3.3 · 5 · 12 · 15 · 24	3000	-40°C~70°C	52.5 x 27.5 x 23.5 CE RoHS CB	3-Year
	AKC		Class I	90~264	Single 3.3 · 5 · 7.35 · 9 · 12 · 15 · 24 Dual ±5 · ±12 · ±15 Triple 5/±12 · 5/±15	3000	-25°C~70°C	69.5 x 47.5 x 21.7 CE RoHS CB	3-Year
	MZC20		Class II	90~264	Single 12 · 24	4000	-40°C~80°C	52.5 x 27.5 x 23.5 CE RoHS CB	3-Year
25W	AFCH25		Class II	90~305	Single 5.1 · 12 · 15 · 24	4000	-40°C~70°C	52.5 x 27.5 x 23.5 CE RoHS CB	3-Year
30W	ATC30		Class II	90~305	Single 3.3 · 5 · 12 · 15 · 24	3000	-40°C~70°C	64.1 x 45.6 x 23.5 CE RoHS CB	3-Year
	ATCH30		Class II	90~305	Single 5.1 · 12 · 15 · 24	4000	-40°C~85°C	64.3 x 45.1 x 21.7 CE RoHS CB	3-Year
	MTC30		Class II	90~264	Single 5 · 12 · 15 · 24	4000	-40°C~80°C	64.1 x 45.6 x 23.5 CE RoHS CB	3-Year
40W	AJC		Class II	90~264	Single 3.3 · 5 · 9 · 12 · 15 · 24 Dual ±5 · ±12 · ±15 · 5/12 · 5/24 Triple 5/±12 · 5/±15	3000	-40°C~70°C	89.5 x 64.1 x 25.0 CE RoHS CB	3-Year
	ANC50		Class II	90~264	Single 5 · 12 · 15 · 24 · 48	3000	-40°C~70°C	74.1 x 54.1 x 21.8 CE RoHS CB	3-Year
50W	ANCH50		Class II	90~305	Single 12 · 15 · 24	4000	-40°C~70°C	74.2 x 47.0 x 23.1 CE RoHS CB	3-Year
	AEC60		Class I	90~264	Single 5 · 9 · 12 · 15 · 24 · 48	4000	-40°C~70°C	109.0 x 58.5 x 30.0 CE RoHS	3-Year
	ARC60		Class II	90~264	Single 12 · 15 · 24	4000	-40°C~85°C	74.2 x 47.0 x 23.1 CE RoHS CB	3-Year
60W	MSC60		Class II	90~264	Single 5 · 9 · 12 · 15 · 24	4000	-40°C~80°C	89.0 x 63.5 x 27.0 CE RoHS CB	3-Year
	AQC100		Class I	90~264	Single 12 · 15 · 24 · 48	3000	-25°C~70°C	109.0 x 58.5 x 30.0 CE RoHS CB	3-Year